

REVISED

A

8

c.

D

E

100

7.01



16

1

D

1

F

STYLE NO.		CATALOG NO.		OUTER INSULATING ENVELOPE COLOR		INSULATION CLASS kV		BASIC IMPULSE LEVEL kV		MAX. TO GROUND VOLTAGE kV		CONNECTION METHOD AND CONTINUOUS CURRENT A @ 60Hz			MINIMUM CREEP DISTANCE in. / [mm]		MINIMUM ARCING DISTANCE in. / [mm]		MAXIMUM ALTITUDE ft / [m]		MOUNTING ANGLE FROM VERTICAL deg		APPROX. WEIGHT lb / [kg]												
												DRAW-LEAD			INBOARD END																				
															TRANS.		O.C.B.																		
025W2000BE		W17B250BB		GRAY						16		N/A			2000		N/A		21.971 [558]		12.289 [312]		10000 [3048]		0 TO 60		96 [43.5]								
025X2000BE		W17B250		BROWN		25		150																											
REVISONS		No. 1 Loc.		1		2		3		4		5		6		7		8		9		10		11		12									
4		CSR 0510684 Y03 = AB HYBRID T. KURLMAN 20 APR 05		5		-ACTIVE- SPACING DIMENSION CHG'D FROM VARIABLE "E" TO ACTUAL VALUE. W.A. SHINER 7-19-05		6		-ACTIVE- DIM CORRECTIONS T. KURLMAN 10 JUL 06		7		-ACTIVE- DIM CORRECTIONS T. KURLMAN 10 JUL 06		8		MIN. ARC WAS 12.039 WT. WAS 96. PERMITS 03/13/07 WILLIAMS 03/13/07		9		-ACTIVE- DIMENSION CHG'D CHG'D SLIGHT BORE EXPANSION CHAMBER & SPRING ASSEMBLY. C. DILLER 08/19/09 D. POLLARD 11/13/10		10		-ACTIVE- CHG'D TUBE EXTEN & CONDUCTOR BACK TO VERSION 8; CHG'D EXPAN CHAMBER; CHG'D 2.895 TO 3.033. C. DILLER 01/15/10 D. POLLARD 01/15/10		11		-ACTIVE- LENGTH OF TOP TERM USABLE THREAD ADDED: GENERAL DRG CLEAN-UP: W.A. SHINER 4-22-10 D. POLLARD 4/22/10		12			